





## SR 45 M E-4

ALL STEEL RADIAL



The EARTHMAX SR 45 M is an all steel radial tire specially designed for rigid haul trucks. SR 45 M provides optimum traction and is ideal for operation in long hauls





## SR 45 M *E-4*



Steel Casing and Steel Belts provide excellent stability and resistance to snags and punctures.

Specially designed tread pattern to minimize vibration and noise

Special rubber compounds for optimal combination of wear and cut resistance.



E-4 tread for long wear life.

Available in cut-resistant, heat resistant or standard specifications

Squared shoulder maximizes ground contact for excellent maneuverability and handling.

Size	Pattern	TRA	Star/ Ply	Туре	CMPD	Rim/ Flange	Unloaded Inflated Dimensions <u>+</u> 2%		Tread Depth	Load Capacity Transport 50 km/h (30 mph)		
							SW (mm)	OD (mm)	OTD mm (mm)	Max. Load (Kg)	Inflation Pressure (bar)	ТКРН
24.00R35	SR 45 M	E-4	**	TL	CR	17.00/3.5	664	2180	70	18500	7	315
24.00R35	SR 45 M	E-4	**	TL	STD	17.00/3.5	664	2180	70	18500	7	390
24.00R35	SR 45 M	E-4	**	TL	HR	17.00/3.5	664	2180	70	18500	7	435

