



**NEW PRODUCT RELEASE**  
**JANUARY 2015**



- SIZE** : 9.5L-15SL, 11L-15SL, 12.5L-15SL
- PATTERN** : I - 1 Stubble Resistant
- CATEGORY** : Farm Implement Tires
- APPLICATION** : Farm Implements
- FEATURES** :
- Multi – Rib, Low profile I-1 tire designed to provide flotation, minimum compaction and excellent load distribution
  - Strong casing for heavy loads and long service life
  - Stubble resistant tread compound
  - Ideal tire for modern farming



Tire Size	Pattern	Ply Rating	Type	Rim		Unloaded inflated Dimensions ± 2.0 %		Static Loaded Radius (mm)	Rolling Circumference ± 2.5 % (mm)	LOAD DATA		
				Rec.	Alt.	Section Width (mm)	Overall Diameter (mm)			SPEED (kmph)	LOAD (kgs)	PRESSURE (bar)
9.5L - 15SL	FARM IMPLEMENT I - 1 (STBL RST)	8	TL	7.00	8 LB	241	765	340	2242	65	1120	3.00
11L - 15SL	FARM IMPLEMENT I - 1 (STBL RST)	8	TL	8 LB	10 LB	270	770	342	2256	65	1150	2.50
11L - 15SL	FARM IMPLEMENT I - 1 (STBL RST)	12	TL	8 LB	10 LB	270	770	342	2256	65	1450	3.60
12.5L - 15SL	FARM IMPLEMENT I - 1 (STBL RST)	12	TL	10 LB	---	325	820	362	2403	65	1750	3.60