



GROWING TOGETHER

**EARTHMAX**  
RADIAL OTR TIRES

# SR53 L-5

***ALL STEEL RADIAL***



SR 53 is an all steel radial tire specially designed for loader or dozer operating in sever rocky conditions including in some cases underground operations. The deep L-5 tread extends wear life & the tread is designed for excellent self-cleaning.



# SR53 L-5

Extra Deep Tire specially designed for loader & dozer service

Extra deep tread and customized compound deliver extended tread wear and also provide resistance to rock cuts & punctures



Suitable for severe rocky condition

Tread pattern is specially designed for self-cleaning

Tire Size	Pattern	Ply/Star Rating	Load Index/Speed Symbol	TRA Type Code	Type	Rim		Unloaded Inflated Dimensions ± 2.0%		Static Loaded Radius 2.0% (mm)	Rolling Circumference ± 2.5% (mm)	LOAD DATA		
						Rec.	Alt.	Overall Width (mm)	Overall Diameter (mm)			SPEED (kmph)	LOAD (Kgs)	INFL. (Bar)
17.5R25	SR 53	*	176/A2	L-5	TL	14.00/1.5	14.00LR/1.5, 13.00LR/1.4	435.0	1400.0	637.0	4214	10.0	7,100	5
20.5R25	SR 53	*	186/A2	L-5	TL	17.00/2.0	17.00AL/1.7	705.0	1550.0	705.0	4666	10.0	9,500	5
23.5R25	SR 53	*	195/A2	L-5	TL	19.5/2.5	-	758	1666	758	5015	10.0	12150	5